

Type	Wire Gauge (SWG)		Barb Distance (mm)	Barb Length (mm)
Electric Galvanized Barbed Wire;	10# x 12#		75-150	15-30
	12# x 12#		75-150	15-30
	12# x 14#		75-150	15-30
	14# x 14#		75-150	15-30
Hot-dip Galvanized Barbed Wire	14# x 16#		75-150	15-30
	16# x 16#		75-150	15-30
	16# x 18#		75-150	15-30
PVC coated barbed wire;	Before Coating	After Coating	75-150	15-30
	1.3mm - 3.5mm	1.8mm - 4.0mm	75-150	15-30
PE barbed wire	BWG 17# - 10#	BWG 15# - 8#	75-150	15-30
	SWG 17# - 10#	SWG 15# - 8#	75-150	15-30









Colours & sizes can be customized upon request.



Barbed Wire

Razor Wire

Outside Diameter	No. of Loops	Standard Length per Coil	Type	Notes
450 mm	33	8m	CBT-65	Single coil
500 mm	41	10m	CBT-65	Single coil
700 mm	41	10m	CBT-65	Single coil
960 mm	53	13m	CBT-65	Single coil
500 mm	102	16m	BTO-10.15.22	Cross type
600 mm	86	14m	BTO-10.15.22	Cross type
700 mm	72	12m	BTO-10.15.22	Cross type
800 mm	64	10m	BTO-10.15.22	Cross type
960 mm	52	9m	BTO-10.15.22	Cross type

Ref. No.	Blade Style	Thickness (mm)	Wire Dia. (mm)	Barb Length	Barb Width	Barb Spacing
BTO-10		0.5±0.05	2.5±0.1	10±1	13±1	26±1
BTO-12		0.5±0.05	2.5±0.1	12±1	13±1	26±1
BTO-18		0.5±0.05	2.5±0.1	18±1	15±1	33±1
BTO-22		0.5±0.05	2.5±0.1	22±1	15±1	34±1
BTO-28		0.5±0.05	2.5	28±1	15	45±1
BTO-30		0.5±0.05	2.5	30±1	18	42±1
BTO-60		0.6±0.05	2.5±0.1	60±2	32±1	100±2
BTO-65		0.6±0.05	2.5±0.1	65±2	21±1	100±2