



Medium Expanded Metal

Medium Expanded Metal mainly for civil engineering batch of cement, machine guard, Highway guardrail, decorative screen, green wall, ceiling, etc.

Material : Ordinary carbon steel plate, stainless steel, iron, copper, aluminum, titanium, nickel plate.

Hole Shape: Hexagon, diamond, shaped plate.

Thickness: 0.3-8.0mm

Mesh Ref.	Material	Mesh Opening (mm)		Thickness (mm)	Strand Width (mm)	Weight (Kg/m2)
		SWM	LWM			
AMM1230	Steel	12	30	3	3	11.8
AMM1538	Steel	15	38	3	5	15.7
AMM3035	Steel	22	57	3	3	6.9
AMM3045	Steel	35	76	3	4.5	6.6
AMM3060	Steel	42	115	3	6	8
AMM3050	Steel	50	152	3	5	4.71
AMM5050	Steel	50	152	5	5	7.05

Balustrade Mesh

Balustrade mesh is ideal for balustrade infill, such as stair balustrade, balcony balustrade and passage balustrade etc.

Mesh Ref.	Material	Mesh Opening (mm)		Thickness (mm)	Strand Width (mm)	Weight (Kg/m2)
		SWM	LWM			
ABM3032	Steel	25	40/81	3	3.2	6.05
ABM3032A	Aluminium	25	40/81	3	3.2	2.09
ABM3033	Steel	30	50/110	3	3.3	5.9

Note: All thickness, strand and weight are subject to +/-10% tolerance

Louvre Mesh